


calculators & organizers



handy and functional electronic devices



# **SHARP**

SHARP Innovations Continually Write New Chapters into the Pages of History.

**Development and mass** 

world's first all-transistor

production of the

desktop calculator.

Forty years ago, SHARP gave 1964 the world its first electronic desktop calculator, now on Development of the world's first electronic display at the National Mudesktop calculator incorporating ICs. seum of Science & Industry as an innovative milestone. World's 1st Succeeding generations carry on this trailblazing spirit, generating a remarkable stream of SHARP original creations. 1969 1964 **SHARP's History** with Calculators 1966 1973 and Organizers World's 1st World's 1st World's 1st

Marketing of the world's

first electronic calculator

incorporating ELSIs.

Development and


introduction of the

world's first super-

card-sized calculator.


thin (1.6 mm)

Since the introduction of the first electronic desktop calculator, SHARP has led the way in the field of calculator technology. A history of superior engineering, advanced functions, and innovative technologies has made SHARP calculators and organizers the choice in all fields, the world over. And this year, we celebrate 40 years since the development of one of our many original creations: the world's first alltransistor desktop calculator.





Euro Convertion



Display illuminates for easy use in dark or poor lighting conditions.




Synchronisation of your organizer and PC PIM data allows for easy one-step integration



Displays information and guidance in one of several selectable languages.



The telephone file has a nameable directory. Stored telephone numbers are displayed with other information



The e-mail file has a nameable directory. Stored e-mail addresses are displayed with



See the entire week's scheduled activities. Enter appointments by day.



The memo function is ideal for structuring and organising ideas within an overview of



The customisable clock displays home and world times, including daylight saving time (summer time) on a 12- or 24-hour basis.



The conversion mode lets you convert currencies or measurements by simply touching a button.



Store items and prioritise them on the To Do



Built-in games turn the pocket databook into an entertainment centre



Check the spelling of English words against suggested matches.



The Diet Function uses the built-in pedometer to keep track of calories burned. It also helps you to calculate your daily caloric intake.



Lets you conveniently select items from the menu screen.



Durable hard case protects calculator from damage.



Features easy key-in for algebraic

Direct Algebraic Logic



Allows users to check the equation and answer at the same time



Recalls any of the last 142 steps.



Eliminates the need to re-enter the constant when doing repeated calculations



Allows the previous answer to be used in the next calculation.

**Chain Calculation** 



Allows you to easily find the answer to derivative calculations.



Allows you to easily find the answer to integral calculations.



Formulas or equations can be stored to simplify calculations.



For easier reading of long, multi-digit numbers, "," or " ' " is inserted for each group of three digits.



Enables quick input of a keystroke, even if you still have a finger on the previous key.



Batteries provide back-up to solar power when light source is interrupted.



Includes handy wallet cover for extra protection and easy storage.



Easy-to-read large digital display reduces eye strain, preventing errors.



Automatically calculates the total sum of amounts generated.



Adjustable angle for personal préference



Fixed angle to ensure optimum



Raises calculator to an ideal Kick Stand operating angle for easier data entry.



Resumes operations after the Auto Power-Off Function has taken effect.



Resume Function plus Line Counter and Condition Symbol.

**Resume Plus** Functio



An "OK" sign appears when the calculation being checked matches the



Calculates average of inputted data.



Calculates prices with or without taxes.

**±TAX** Tax Calculation



Determines the number of days and a specific date from inputted dates.

Day/Date Calculation

2-COLOUR PRINT

Printed report is easy to read with red ink used for negative.



3 rates can be converted easily with the touch of a button.



Easy conversion of units such as currencies, based on an adjustable rate set by the user.



Fits easily in the palm of your hand.



Quick and convenient calculation of cost, selling price and margins; ideal for business transactions.



Comes with attached hard cover for extra protection and durability.



Long-life plastic buttons.

	Product Line-Up	Index	
	Digital Voice Recorder	Page 6 PA-VR5E PA-VR10E PCE	Didital Voice Recorder
	Electronic Organizers	Page 7 ZQ-P20H ZQ-P10	Electronic Organizer
	Scientific Calculators	Page 8 - 10 EL-501WWH, EL-506WWH, EL-520WWH, EL-531WHWH, EL-5250	Scientific Calculators
	Printing Calculators	Page 11 EL-2607P, EL-2901PIII EL-1801C, EL-1611P	Printing Calculators
Sha sail S	Office Calculators	Page 12 - 14 EL-2125C, EL-338G, EL-337C, EL-421M, EL-334F, EL-332A, EL-310A, EL-M700G, EL-M711G	Office Calculators
Se of the second	Persomal Calculators	Page 15 - 16 EL-250S, EL-233S, EL-480SR EL-W211G, EL-376S, EL-243S,	Personal Calculators
	Kids´ Calculators	Page 17 EL-S10 BPK/BBL	Kids′ Calculators
	14 Digit Calculators	Page 17 EL-145A EL-144A EL-143S	14 Digit Calculators
	Specifications & Merchandising Information	Page 18 - 25	Specifications Merchandising- information

# Digital Voice Recorders



# The Handy, High-Capacity Voice Recorder

Whether it's a week-long business trip or a weekend seminar, there's one personal assistant you can't afford to leave behind. One tool that frees you from constant note-taking, and allows you to get more involved in the discussion. Meet the slender, palm-fitting PA-VR10EPCE/5E digital voice recorder from SHARP. With the PA-VR10E PCE, you can record approximately 28 hours of meetings, lectures, or memos (approximately 14 hours for the PA-VR5E). Now bothersome, low-capacity cassettes are a thing of the past. Instead, you get reliable, extended voice recording and a host of practical conveniences. The PA-VR10EPCE/5E from SHARP — putting longer recording within your grasp.

## PA-VR10EPCE, PA-VR5E

- 28 (PA-VR10EPCE)/14 (PA-VR5E) hours (approx.) recording capacity (LP mode)
- 4 folders: up to 127 separate files
- Personalised alarm
- Timer recording
- Timer stamp
- 2 microphone sensitivity settings
- Dimensions: 31 (W) x 111 (D) x 16.8 (H) mm
- Weight: approx. 66 g (w/ batteries) (PA-VR10EPCE) approx. 65 g (w/ batteries) (PA-VR5E)



PA-VR5E

PA-VR10EPCE

# An Array of User-Friendly Features

#### Time Stamp & Event Marking

The Time Stamp feature automatically marks each recording with the time and date, so you can keep track of your recordings more effectively. Event Marking, meanwhile, lets you "bookmark" relevant moments during a meeting or presentation, so you can find them more easily when you later review the recording. Up to 50 Event Marking numbers can be inserted into each file.

#### Schedule Recording

You needn't worry about forgetting to press the record button for a lesson, meeting or presentation. Schedule Recording allows you to preset the unit to record for a specified time period. This way, you can leave the unit unattended in a classroom or meeting location and still get the recording you need.

#### Message Alarm

Stay on top of your busy schedule, with the PA-VR10EPCE/5E's customizable alarm. Instead of a generic alarm tone, you can record a message to be played back at the time of your choosing. A customized message gives you a more detailed reminder about that important event or appointment. As many as 3 different alarms can be set at one time.

#### USB Connectivity (PA-VR10EPCE only)

The PA-VR10EPCE comes with a handy USB port that enables connection to a PC. USB connectivity allows you to easily transfer recorded files to your PC for data back-up.\*

\* The PA-VR10EPCE supports IBM PC/AT-compatible computers using one of the following operating systems: Microsoft® Windows® XP Professional/XP Home/Me/2000 Professional/98/98SE. One USB port (version 1.1 or above) is required to connect your PC to the digital voice recorder. A commercially available USB (A) male-USB (Mini-B) male cable is supplied in the package.

 $Note: If your \ PC \ is \ running \ Windows \ 98 \ or \ 98SE, you \ will \ need \ to \ install \ a \ dedicated \ USB \ driver \ included.$ 

#### Stylish Design

The see-through acrylic face of the PA-VR10EPCE/5E provides more than just robust protection for the LCD screen; it also provides an elegant finishing statement. The centrally-located scroll wheel, meanwhile, offers design simplicity as well as effortless one-handed operation.



#### Other Features

- Clock Mode Screen (M/D, h:m:s) File Skip FF/FR
- $\bullet$  3-Way Speed Control (Fast/Reg/Slow)  $\bullet$  Repeat Function  $\bullet$  Voice Activation Function
- • 2 Microphone Sensitivity Settings  $\left(HIGH/LOW\right)^{*}$  • Hold Function
- \* The high-sensitivity mode (HIGH) enables you to record peripheral sound in addition to your intended target sound. The normal sensitivity mode (LOW), meanwhile, is ideal for dictation.

# **Electronic Organizers**



## **ZQ-P10**

- Power source: CR2032 x 1
- Dimensions: 64 (W) x 97 (D) x 14.8 (H) mm 2-17/32" x 3-13/16" x 19/32"
- Weight: approx. 72 g
- Memory at 96KB equivalent. approx. 1,500 telephone names & numbers (name, telephone and fax number are 14 characters per entry) can be stored by using compression technology. (Compression rate approx. 1.5:1)



ZQ-P10 (Blister Back) 4 974019 023632



## ZQ-P20H


- Power source: CR2032 x 2 (Main/Backlight)
- Dimensions: 69,8 (W) x 109,3 (D) x 16,3 (H) mm 2-3/4" x 4-5/16" x 21/32"
- Weight: approx. 104 g
- An English version of Microsoft® Outlook® 98/2000/ 2002/2003 must be installed to utilize the synchronisation software. \*\*The PC Software is intended to run on a PC with an Englisch version of Microsoft® Windows® 98/98SE/2000 Professional/Me/XP Home/XP Professional.



0

Includes PC-Link cable with serial port connector and software\*\* English model only

Diet Function (ZQ-P20H)



ZQ-P20H (clamshell) 4 974019 024189

#### Synchronise with Microsoft® Outlook®\* (ZQ-P20H)

• Synchronise contact information with your PC.


#### Tel Schedule To Do Memo Microsoft® Outlook®\* Synchronisation USB PC-Link cable (included) (N.B. ZQ-P20H requires included PC-Link cable.) English version of Microsoft® Windows® PC ZQ-P20H


# Multi-Language Guidance Message (ZQ-P20A, ZQ-P10A EL-6053S)

10-Language (ZQ-P20A, ZQ-P10A)

English, German, Spanish, French, Italian, Portuguese, Czech, Greek\*, Hungarian, Polish

\* Only capitalized letters can be entered in Greek Mode.






downloadable food database on the included CD-ROM. (N.B. Only the ZQ-P20H handles other nutritional data.)

• Compare with previous records of calories taken in or burned.

The unit may not count steps correctly if you:

- Walk at an irregular pace, or in a crowded place.
  Shuffle legs excessively.
- · Wear sandals when walking.
- Vary your movement (play sports, for example). Move up/down excessively.
- Are in a vehicle with vertical and horizontal motions. • Attach the unit improperly (tilted, for example).





STEP


150.

- An English version of Microsoft® Outlook® 98/2000/2002/2003 must be installed to utilize the
- The PC software is intended to run on a PC with an English version of Microsoft® Windows® 98/98SE/2000 Professional/Me/XP Home/XP Professional.

# Greater Efficiency and Ease of Use ADVANCED D.A.L.

#### Direct Algebraic Logic (D.A.L.) D.A.L.

Until the introduction of SHARP's D.A.L., keying in equations had been a complicated process making scientific calculators difficult to use. Introduced in 1992 and an industry-first, SHARP's D.A.L. allows symbols and numbers of an equation to be entered as they are written. Instead of wasting energy on difficult calculator operations, users are free to concentrate on mathematical concepts.



#### 2-Line Display

2-Line

A 2-line display allows the users to check the equation and answer at the same time. Because the equation remains on display, it is easy to edit or make substitutions if necessary.



#### Multi-Line Playback




SHARP's Multi-Line Playback function lets you recall any of the last 142 steps you have made. This feature is very useful for comparing formulas and recalculating equations.

#### • Comparative learning

Calculation A (with parentheses)

Calculation B (without parentheses)



Edit (sin to cos)


The equations are different, but the answers are the same

#### • Edit and recalculate

Calculation A

Calculation A





Change the previous equation and recalculate

#### Constant/Chain Calculations



Constant and Chain Calculation functions are popular in general electronic calculators as they allow equations to be entered without having to key repeatedly. Confusion may arise however, as not all scientific calculators show the equation being equal to the answer in the formula display. With SHARP's scientific calculators, the figures you omit are automatically shown as K (constant) or ANS (answer)\*. Contradictions between equations and answers are eliminated and calculations are easier and more logical to enter.


\* EL-500W and EL-510R do not display "K" or "ANS"

#### • Constant Calculation



A portion of the equation is automatically memorised as a constant, thus omitting redundant input.

#### • Chain Calculation



The answer can be used as is in the next calculation.


(Example using EL-506W.)

#### Numerical Derivative/Integral

d/dX

∫ dX


Simply enter numerical values following the interactive on-screen instructions, and you can find the answer easily of derivative and integral calculations. You don't have to re-enter the formula, and the calculation can be repeated as many times as needed.







You can calculate the same derivative calculation repeatedly without having to input the formula again.



You can calculate the same integral calculation repeatedly without having to input the formula again

#### Formula Memory

■-F1■-F3

Frequently used formulas or complex equations can be stored as functions in Formula Memory\*. By recalling the formula, you can substitute new variables into the equation and recalculate it without having to enter the entire sequence again. Since you can do repeat equations, it's also convenient for simulations.

\*Formulas up to 256 characters in length can be stored in F1–F4.

## (1) Store the equation into the calculator.



Note: Even when the power is off, the equation will remain in memory until a new equation is stored.

# (2) Call up the equation. RCL F1 (3) Use the equation to calculate. 2ndF ALGB 10 =



#### **Solver Function**


This function enables calculation of a variable  $\kappa$  in a given equation. Other variables (a, b, c, etc.) must already be defined in order to calculate  $\kappa$ .

Equation " $\sin x - 0.5$ " (DEG)



#### **Matrix Function**

In addition to the four basic arithmetic functions (excluding division between matrices),  $x^3$ ,  $x^2$ , and  $x^4$ , users are provided with transpose and cumulative matrix functions, among others. Up to four matrices can be saved in memory, each up to four rows by four columns in size.



# **Scientific** Calculators

#### Standard





## EL-506WWH

- Power source: Twin power (Solar & LR44 x 2)
- Dimensions: 79.6(W) x 154.5(D) x 13.2(H) mm 3-1/8" x 6-3/32" x 17/32"
- Weight: approx. 97 g

Matrix/list calculations Constant/chain calculations Multi-line playback Solver function Matrix function Sturdy, stylish design















## EL-520WWH

- Power source: Twin power (Solar & LR44 x 2)
- Dimensions: 79.6 (W) x 154.5 (D) x 13.2 (H) mm 3-1/8" x 6-3/32" x 17/32"
- Weight: approx. 97 g

Constant/chain calculations Multi-line playback Solver function Sturdy, stylish design



EL-520WWH

4 974019 024035















## EL-531WHWH

- Power source: R6 (AA) x 1
- Dimensions: 79.6 (W) x 154.5 (D) x 18.2 (H) mm 3-1/8" x 6-3/32" x 23/23"
- Weight: approx. 110 g

Constant/chain calculations Multi-line playback Sturdy, stylish design











EL-531WHWH 4 974019 023984



# EL-501WWH

- Power source: LR44 x 2
- Dimensions: 78.6 (W) x 144 (D) x 11.6 (H) mm
- 3-3/32" x 5-21/32" x 15/32" Weight: approx. 75 g

Constant/chain calculations

Stylish design





EL-501WWH (Box + Strap) 4 974019 023908





# EL-5250

- Programmable up to 4,096 steps
- Solver function
- Power source: CR2032 x 2
- Dimensions: 79.6 (W) x 154.5 (D) x 15.2 (H) mm
- 3-1/8" x 6-3/32" x 19/32" Weight: approx. 97 g



















## CS-2635RH

- Printing speed: 4.3 lines/sec.
- Power source: AC only
- Dimensions: 250 (W) x 345 (D) x 78 (H) mm
- Covenient 2-memory stystem (M&I memory)
- Weight: approx. 2.000 g

# **Printing Calculators**









CS-2635RH 4 974019 023564





## EL-2607P

- Printing speed: Approx. 4.3 lines/sec.
- Power source: AC only
- Dimensions: 222 (W) x 327 (D) x 78 (H) mm 8-3/4" x 12-7/8" x 3-1/16"
- Weight: approx. 1,900 g













EL-2607P (Box) 4 974019 023663



## EL-2901PIII

- Printing speed: 2.1 lines/sec.
- Power source: AC only
- Dimensions: 193 (W) x 256 (D) x 62.5 (H) mm 7-19/32" x 10-3/32" x 2-15/32"
- Weight: approx. 1,000 g















#### EL-1801C

- Printing speed: 2.1 lines/sec.
- Power source: DC/AC
  - (AA x 4, AC adapter optional)
- Dimensions: 170 (W) x 231 (D) x 57.5 (H) mm 6-11/16" x 9-15/16" x 2-1/4"
- Weight: approx. 580 g



EL-1801E

Only for Hungary, Czech

# Semi Desktop

12-Digit







EL-1801C (Box + Strap) 4 974019 009247



Internal Paper-Roll Supply

External Paper-Roll Supply

# EL-1611P

- Printing speed: 1.6 lines/sec.
- Power source: DC/AC
- (AA x 4, AC adapter optional)
- Dimensions: 96 (W) x 191 (D) x 40 (H) mm 3-3/4" x 7-1/2" x 1-9/16"
- Weight: approx. 315 g



|EL-1611E

Only for Hungary, Czech

# Semi Desktop







EL-1611P (Box + Strap) 4 974019 009292



## EL-2125C

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 140 (W) x 195 (D) x 22.5 (H) mm 5-19/32" x 7-21/32" x 29/32"
- Weight: approx. 215 g



Only for Hungary, Czech





GTFUNCTION







EL-2125C (Box+Strap) 4 974019 022772



# EL-338G

- Twin power (Solar cell & LR44 x 1)
- Dimensions: 135 (W) x 200 (D) x 17 (H) mm 5-5/16" x 7-7/8" x 21/32"
- Weight: approx. 220 g



Only for Hungary, Czech













EL-338G (Box+Strap) 4 974019 024462







## EL-337C

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 108 (W) x 175 (D) x 22 (H) mm 4-7/32" x 6-7/8" x 7/8"
- Weight: approx. 165 g



EL-337E

Only for Hungary, Czech

#### Nice Size

12-Digit



















EL-337C (Box + Strap) 4 974019 022758



### EL-421M

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 108 (W) x 170 (D) x 15 (H) mm 4-1/4" x 6-11/16" x 19/32"
- Weight: approx. 160 g

















EL-421M (Box + Strap) 4 974019 023175

#### **Convenient Functions**



#### **Resume Function**

To resume operations after the Auto Power-Off Function has taken effect, press the Resume key. The display will return to the calculation that was in progress, providing the following indicator:
• Function Symbol: indicates the last function used in the calculation.



Resume Plus (Resume Function plus Line Counter and Condition Symbol)

Adds the following indicators as well as Resume Function:


- Line Counter: shows number of figures entered.
- Condition Symbol: indicates the next figure should be entered.





#### **Answer Check**

An "OK" sign appears when the checking calculation matches the result of the first.





#### **Tax Calculation**

Easily calculates prices with or without taxes.



#### Day/Date Calculation

- Day Calculation: determines number of days between two dates.
- Date Calculation: determines the date after a number of days and a starting date have been entered.



## **EL-334F**

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 108 (W) x 170 (D) x 15 (H) mm 4-1/4" x 6-11/16" x 19/32"
- Weight: Approx. 160 g



EL-334E

Only for Hungary, Czech















EL-334F (Box + Strap) 4 974019 022734



They make life a lot simpler.

## **EL-332A**

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 101 (W) x 142 (D) x 34 (H) mm 3-31/32" x 5-19/32" x 1-11/32"
- Weight: approx. 115 g













EL-332A (Box + Strap) 4 974019 022796



## **EL-310A**

- Power source: Twin power (Solar cell & LR1130 x 1)
- Dimensions: 87 (W) x 116 (D) x 20 (H) mm 3-13/32" x 4-9/16" x 25/32"
- Weight: approx. 76 g











EL-310A (Box + Strap) 4 974019 009490



## **EL-M700G**

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 87 (W) x 116.5 (D) x 28.5 (H) mm 3-7/16" x 4-19/32" x 1-1/8"
- Weight: approx. 85 g















EL-M700G (Window box + Strap) 4 974019 023717



## **EL-M711G**

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 100 (W) x 151.5 (D) x 33 (H) mm 3-15/16" x 5-31/32" x 1-5/16"
- Weight: approx. 130 g



Only for Hungary, Czech

















EL-M711G (Window box + Strap) 4 974019 023755



#### **EL-250S**

Protective Display Cover

Personal

**Calculators** 

- Power source: Twin power (Solar cell & LR1130 x 1)
- Dimensions: 71 (W) x 116 (D) x 16.5 (H) mm 2-25/32" x 4-9/16" x 21/32"
- Weight: approx. 58 g



**EL-250E** 

Only for Hungary, Czech













EL-250S (Box + Strap) 4 974019 022215



## **EL-233S**

- Power source: LR1130 x 1
- Dimensions: 60 (W) x 103 (D) x 8.3 (H) mm 2-3/8" x 4-1/16" x 5/16"
- Weight: approx. 35 g



**EL-233E** 

Only for Hungary, Czech







EL-233S (Box + Strap) 4 974019 023014



## EL-480SR

- Recall function
- Power source: Twin power (Solar cell & LR1130 x 1)
- Dimensions: 69 (W) x 119 (D) x 7.1 (H) mm 2-23/32" x 4-11/16" x 9/32"
- Weight: approx. 65 g (including wallet)











EL-480SR (Box + Strap) 4 974019 021881



#### **EL-W211G**

- Power source: Twin power (Solar cell & CR2016 x1)
- Dimensions: 70 (W) x 117 (D) x 8.1 (H) mm 2-3/4" x 4-19/32" x 5/16"
- Weight: approx. 56 g
















EL-W211G (Window box + Strap) 4 974019 023694





## **EL-376S**

- Power source: Twin power (Solar cell & LR1130x1)
- Dimensions (closed): 72 (W) x 115 (D) x 12 (H) mm 2-13/16" x 4-17/32" x 15/32"
- Weight: approx. 66 g



EL-376E

Only for Hungary, Czech









EL-376E (Box + Strap) 4 974019 009537



# **EL-243S**

- Power source: Twin power (Solar cell & LR1130x1)
- Dimensions (closed): 64 (W) x 105 (D) x 11 (H) mm 2-1/2" x 4-5/32" x 7/16"
- Weight: approx. 51 g









EL-243S (Box + Strap) 4 974019 009575

#### For More Colourful Calculations

With basic arithmetical functions and large, easy-to-read displays, the EL-S10 is a joy to use. The light and compact EL-S10 has a protective cover, so you can take it anywhere. it features practical, easy-to-click plastic keys and cute, colourful designs that are fun for everybody, not just for kids.

## EL-S10 BPK/BBL

- Power source: LR1130 x 1
- Dimensions: 70 (W) x 107 (D) x 10.5 (H) mm (Closed)
  - 2-3/4" x 4-7/32" x 13/32"
- Weight: approx. 54 g















EL-S10 BPK 4 974019 024936 EL-S10 BBL 4 974019 024929







## 14 Digit Calculators

## EL-145A

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 110 (W) x 168 (D) x 15 (H) mm 4-11/32" x 6-5/8" x 19/32"
- Weight: approx. 160 g















EL-145A (Box + Strap) 4 974019 024325



# **EL-144A**

- Power source: Twin power (Solar cell & LR44 x 1)
- Dimensions: 102 (W) x 148 (D) x 15 (H) mm 4-1/32" x 5-13/16" x 19/32"
- Weight: approx. 125 g

#### Mini Nice Sice



DISPLAY/













EL-144A (Box + Strap) 4 974019 024332



## FL-143S

- Power source: Twin power (Solar cell & LR1130 x 1)
- Dimensions (closed): 72 (W) x 115 (D) x 12 (H) mm 2-27/32" x 4-17/32" x 15/32"
- Weight: approx. 66 g

#### Hand-held/Hard cover













EL-143S (Box + Strap) 4 974019 024349

## **Specifications**

Model	PA-VR10EPCE	PA-VR5E	
	LP mode: 28 hours	LP mode: 14 hours	
Recording Time	SP mode: 8.5 hours	SP mode: 4 hours	
	HQ mode: 4 hours	HQ mode: 2 hours	
Internal Memory	64MB	32MB	
Message Alarm	O	U	
Schedule Recording	O	U	
Event Marking	O	U	
Silence Skip Recording	O	U	
Microphone Sensitivity	High/Low	High/Low	
LED Indicator	O	U	
File Repeat	O	U	
File Skip	O	O	
Earphone/Microphone	U/U	0/0	
Recording Method (Monaural)	O	U	
USB Connection	O	_	
USB External Memory	O	_	
Clock Accuracy	Average ±1 min./month (at 25°C)	Average ±1 min./month (at 25°C)	
Power Source	AAA-size alkaline batteries (LR03) x 2	AAA-size alkaline batteries (LR03) x 2	
Dimensions (W x D x H)	31 x 111 x 16.8 mm 1-7/32" x 4-3/8" x 21/32"	31 x 111 x 16.8 mm 1-7/32" x 4-3/8" x 21/32"	
Weight (Approx.)	66 g	65 g	

# **Electronic Organizers**

Мо	del	ZQ-P20H	ZQ-P10
Dis	play	12-column x 3-line	12-column x 3-line
Bac	klight	0	_
Me	mory Capacity	1MB (Flash memory)*1	96KB equivalent*11
Ма	x. Input Characters	36 + 72 + 36 + 36*10	36 + 36 + 36 + 36*10
Ca	pacity Numbers	72*10	72*10
Ke	yboard	_	_
Lov	vercase Letters	O (Except Greek mode)	O (Except Greek mode)
Eur	opean Characters	0	0
Sch	nedule with Alarm	0	0
Cal	endar	_	_
	ephone Directory	2-file	2-file
E-n	nail Address	in Tel directory	in Tel directory
We	b Address (URL)	in Tel directory	in Tel directory
Me	mo	0	0
Home Clock with Alarm		0	0
World Clock		42-city	29-city
Calculation Currency/Unit Conversion		10-digit	10-digit
		0	0
٩nı	niversary	_	_
Spe	ell Checker	O (Approx. 10,000 English words)	_
Enç	lish/Spanish Word Translator	_	_
Gai	ne	0	0
Sec	cret	O*2	O*2
Die	t Function	O*7	_
PC	Link	Included ( Microsoft® Outlook® ) (synchronise capability)	_
Power Source	Main (Approx. Life)	CR2032 x 2 (5,000 hrs.*c, 2,000 hrs.*d, 6 mos.*e)*5	CR2032 x 1 (2 yrs.*h)*5
Ver	Backup	Flash memory	_
Š	Backlight (Approx. Life)	Uses main battery	_
Din	nensions (Closed) (W x D x H)	69.8 x 109.3 x 16.3 mm 2-3/4" x 4-5/16" x 21/32"	64 x 97 x 14.8 mm 2-17/32" x 3-13/16" x 19/32"
We	ight (Approx.)	104 g	72 g
-	9 · ( FF · /	9	

# Specifications

Certain functions will require a PC, optional PC software, add-on software, a cellular phone, a printer, and/or a wireless interface as demanded. Some services listed may not be available in some regions due to existing restrictions.

due to existing restrictions.

\*1 ZQ-590A: 8MB (User area: approx. 8,000KB for data storage)

ZQ-290A: 1.5MB equivalent (User area: approx. 896KB for data storage)

ZQ-P20A: 1MB (User area: approx. 896KB for data storage)

EL-6990P: 256KB (User area: approx. 250KB for data storage)

\*2 Functions differ in each model.

\*3 File attachments cannot be downloaded. Text viewer only. \*4 Downloadable from included CD-ROM.

\*\* To will obtain the more than included CD\*\*(C/7°F). Actual battery life may vary depending on usage.

\*\*a When data is continuously displayed without backlight.

\*b When data is searched for 5 minutes and displayed for 55 minutes per hourly use, and backlight.

- is on for 2 minutes per hourly use. \*c When data is continuously displayed without backlight, with pedometer off.
- \*d When data is searched for 5 minutes and displayed for 55 minutes per hourly use, with pedo meter off.
- \*e While pedometer is on, with 5 minutes of data search, 55 minutes of data display, and 10,000 step counts per day.
- \*f When data is displayed for 30 minutes, alarm on for 20 seconds and key touch tone turned on/off 100 times per day.
  \*g When backlight is on for 10 seconds and off for 50 seconds.

- "6 Memory at 1.5MB equivalent. Approx. 7,000 telephone names & numbers can be stored by using compression technology at a compression rate of approx. 1.5:1. (Names & numbers including home, office, fax, and mobile — are 14 characters per entry, and addresses are 38 characters per entry.)
- \*7 The Diet function features a built-in pedometer. It also enables calculation of the calories, carbohydrates and other nutritional data for 800 different foods (200 foods for the ZQ-P20H, with no other nutritional data).

- Databases are downloadable from the included CD-ROM.

  8 May not be available in some regions as stocks are very limited.

  9 If operating batteries are replaced promptly when exhausted.

  10 Telephone directory mode.

11 Heispitalie united by middle 11 Approx. 1,500 telephone names & numbers (name, telephone and fax number are 14 characters per entry) can be stored by using compression technology. (Compression Rate Approx. 1.5:1)

EL 2008/(ANT) EL 2008/(ANT) EL 21/8/18/18/18

# Specifications (Standard)

M	lodel	EL-506W(WH)	EL-520W(WH)	EL-531WH(WH)	EL-501W(WH)
ķ	Dot Matrix (Digit x Line)	12 x 1	12 x 1	12 x 1	_
Displa	Segment (Mantissa + Exponent)	10 + 2	10 + 2	10 + 2	10 (8 + 2)
Ö	3-Digit Punctuation	0	0	0	_
Ca	lculation Results (Mantissa + Exponent)	10 + 2	10 + 2	10 + 2	8 + 2
M	emory	9	9	9	1
Fı	ınctions	469	419	272	131
	FSE Display	0		0	O (S only)
	Last Digit Correction	0		0	
	Last Answer Memory	0	0	0	_
	π, +/–, EXP	0		0	0
	$y^{x}, \sqrt[x]{y}, x^{2}, \sqrt{\ }, x^{-1}, \sqrt[3]{\ }$	0		0	0
	$\mathbf{x}^3$	0	0	0	_
	ln, log, ex, 10x	0	0	0	0
	sin, cos, tan, sin <sup>-1</sup> , cos <sup>-1</sup> , tan <sup>-1</sup>	0	0	0	0
	sinh, cosh, tanh, sinh-1, cosh-1, tanh-1	0	0	0	0
	n!, nPr, nCr	0	0	0	O (n! only)
	Random	0	0	0	0
	Random Dice	0	0	0	_
	Random Coin	0	0	0	_
	Random Integer	0	0	0	_
	Fraction Calculations	0	0	0	_
	Reduction Study				_
s	Highest Common Factor/Lowest Common Multiple	_		_	_
ion	Quotient and Remainder Calculation	_		_	_
nct	$\rightarrow r\theta, \rightarrow xy, \rightarrow DEG, \rightarrow DMS$	0	0	0	0
Ŀ	Physical Constants	52	52		
	Metric Conversions	44	44	_	_
	Deg, Rad, Grad Modes	0	0	0	0
	Complex Number Calculation	0	0		0
	2-Var./3-Var. Linear Equations	0	0	_	
	Solving Quadratic/Cubic Equations	0	0	_	_
	Multi-Line Playback	0	0	0	_
	Playback	0	0	0	_
	Constant Calculation	0	0	0	0
	Chain Calculation	0	0	0	0
	Numerical Derivative	0	0		
	Numerical Integral	0	0	_	_
	Formula Memory	0	0	_	_
	Algebraic Substitution	<u>o</u>		_	_
	Matrix Calculation	0		_	_
	Solver	0	0	_	_
	List Calculation			_	_
2.	=ਰੋਂ Bin/Pen/Oct/Hex	0	0	0	O*10
M	Logical Operation	0			
icsB	1-Var /2-Var Statistics	0			O*9
tatist	1-Var./2-Var.Statistics Regression Calculations	6*6	6*6	6*6	
	Key Roll-Over	0	0	0	_
	-	Solar/LR44 x 2	Solar/LR44 x 2	R6 (AA) x 1	LR44 x 2
Po	ower Source (Approx. Life)	(5,000 hrs.) *7	(5,000 hrs.)*7	(17,000 hrs.)*7	(3,000 hrs.)*7
_	imensions (W x D x H)	79.6 x 154.5 x 13.2 mm 3-1/8" x 6-3/32" x 17/32"	79.6 x 154.5 x 13.2 mm 3-1/8" x 6-3/32" x 17/32"	79.6 x 154.5 x 18.2 mm 3-1/8" x 6-3/32" x 23/32"	78.6 x 144 x 11.6 mm 3-3/32" x 5-21/32" x 15/32"
W	Veight (Approx.)	97 g	97 g	110 g	75 g

# Specifications (Programmable)

Mo	del	EL-5250
Dot	Matrix Display (Digit x Line)	14 x 3
	culation Results (Mantissa + Exponent)	10 + 2
Mei	mory	27
Fun	ctions	423
	FSE Display	0
	Last Digit Correction	0
	Last Answer Memory	0
	π, +/–, EXP	0
	$\mathbf{y}^{\mathbf{x}}, \sqrt[\mathbf{x}]{\mathbf{y}}, \mathbf{x}^2, \sqrt{}, \mathbf{x}^{-1}$	0
	ln, log, ex, 10X	0
SI	sin, cos, tan, sin-1, cos-1, tan-1	0
Functions	sinh, cosh, tanh, sinh-1, cosh-1, tanh-1	0
] In	n!, nPr, nCr	0
표 [	Random	0
	Fraction Calculations	0
	$\rightarrow$ r $\theta$ , $\rightarrow$ xy, $\rightarrow$ DEG, $\rightarrow$ DMS	0
	Deg, Rad, Grad Modes	0
	Numerical Integral	0
	Playback	0
	Solver	0
) J	Bin/Oct/Hex Modes	0
BIN	Logical Operation	0
stics	1-Var./2-Var.Statistics	0
Stati	Regression Calculations	6*6
oge	Max. Programmes	99
Programme Mode Statistics BIN/OCT/	Max. Steps	4,096
mg [	Programme Titles	0
Prog	Subroutines, Branch	0
Pov	ver Source (Approx. Life)	CR2032 x 2 (1,800 hrs.)*11
Din	nensions (W x D x H)	79.6 x 154.5 x 15.2 mm 3-1/8" x 6-3/32" x 19/32'
Wei	ight (Approx.)	97 g

<sup>\*6</sup> Linear: y = a + bx, Exponential: y = aebx, Logarithmic:  $y = a + b \ln x$ , Power: y = axb, Inverse: y = a + bx-1, Quadratic: y = a + bx + cx2

<sup>\*7</sup> Continuous display. Actual battery life may vary depending on usage.

<sup>\*11</sup>When used continuously for 5 minutes and displayed for 55 minutes per hourly use withtemperature of approx. 25°C (77°F). Actual battery life may vary depending on usage.

# Specifications (Desktop)

# Specifications (Desktop, Semi-Desktop, Hand-Held)

Model		EL-2607P	Mode		EL-2901P III	EL-1801C	EL-1611P
Display	i	12	Displa	ny	12	12	12
Memor		2 (GT)	Backli	ght	-		-
	al Setting	F-6-3-2-1-0	Memo	ory	2 (GT)	1	1
Adding	Mode	U	Decim	nal Setting	F-6-3-2-1-0-A	F-2-0-A	F-3-2-1-0-A
Consta	nt	U	Addin	g Mode	F-0-3-2-1-0-A	r-2-U-A	F-3-Z-1-U-A
Triple 2	Zero Key	_	Const	ant	O	O	O
Double	Zero Key	O	Doubl	le Zero Key	O	O	O
Round	Up/Off/Down	Up/Off/Down	Round	l Up/Off/Down	Up/Off/Down	Off/Down	_
Item C	ounter	O	Item C	Counter	O	O	_
Grand	Total	O	Grand	Total	O		-
Cost/Sell/Margin +Tax/-Tax Calculation Mark Up Conversion Function Average Printing Colours		=	Cost/S	Sell/Margin	O		
		0/0	+Tax/-Tax Calculation  Mark Up  Conversion Function		υ/υ	<u>U/U</u> U	υ/υ –
		U			-		
		_			-		-
		0	Averag	ge	-		-
		2	Printi	ng Colours	2	2	1
Printin	g Speed	4.3 Lines/Sec.		ng Speed	2.1 Lines/Sec.	2.1 Lines/Sec.	1.6 Lines/Sec.
AL CHART	Paper Roll	*	OPTIONAL ACCESSORY CHART	Paper Roll	*	*	EA-7100P (58 x ⊌25)★
OPTIONAL ACCESSORY CHART	Ink Ribbon	¥	DPTION ESSORY	Ink Roller	EA-772R	EA-781R-BK (black) EA-781R-RD (red)	EA-732R
ACCI	Ink Roller	_	ACC	AC Adapter	-	EA-28A	EA-28A
Power	Source	AC		Source	AC	AA x 4/AC*	AA x 4/AC*
Dimen: (W x D		222 x 327 x 78 mm 8-3/4" x 12-7/8" x 3-1/16"	Dimer (W x l	nsions D x H)	193 x 256 x 62.5 mm 7-19/32" x 10-3/32" x 2-15/32"	170 x 231 x 57.5 mm 6-11/16" x 9-15/16" x 2-1/4"	96 x 191 x 40 mm 3-3/4" x 7-1/2" x 1-9/16"
Weight	(Approx.)	1,900 g	Weigh	nt (Approx.)	1,000 g	580 g	315 g

<sup>\*</sup> AC adapter (optional), H Part code: DPAPR1004CSZZ - 5 rolls/pack, 58 (W) x 80 (ø) mm, I Part code: URBNT1007CCZZ - Ink ribbon (black/red)

# Personal **Calculators**

# Specifications (Hand-Held, Hard Cover, Card)

Model	EL-480 SR	EL-W211G	EL-376S	EL-243S
Display	8	10	8	8
3-Digit Punctuation	0	O		
Memory	1	1	1	1
Root	U		U	U
Percent	0	O	0	O
Mark Up				
Sign Change	0		0	O
Constant	U	U	U	U
Metric Conversion	U			
Cost/Sell/Margin				
Decimal Setting				
+Tax/-Tax Calculation	/	0/0	/	/
2-Key Roll-Over		U		
Auto Power Off		O	0	O
Key Material	Rubber	Plastic	Plastic	Rubber
Hard Cover			0	O
Wallet Case	U			
Power Source	Solar 50 Lux	Solar/CR2016 x 1	Solar/LR1130 x 1	Solar/LR1130 x 1
Dimensions (W x D x H)	70 x 122 x 5.9 mm 2-3/4" x 4-13/16" x 7/32"	70 x 117 x 8.1 mm 2-3/4" x 4-19/32" x 5/16"	72 x 115 x 12 mm*5 2-13/16" x 4-17/32" x 15/32"	64 x 105 x 11 mm <sup>°5</sup> 2-1/2" x 4-5/32" x 7/16"
Weight (Approx.)	80 g*/	56 g	66 g	51 g

<sup>\*1</sup> Including wallet. \*2 Excluding wallet. \*3 Continuous LCD display. Actual battery life may vary depending on usage. \*4 When used for 1 hour per day. Actual battery life may vary depending on usage. \*5 When closed.

# Specifications

Model	EL-250S	EL-233S	
Display	8	8	
3-Digit Punctuation	O		
Memory	1	1	
Root		U	
Percent	0	O	
Mark Up			
Sign Change			
Constant	U	U	
Last Answer Memory			
<b>Decimal Setting</b>	F-2-0		
+Tax/-Tax Calculation	0/0	/	
2-Key Roll-Over			
Auto Power Off	U	U	
Key Material	Plastic	Plastic	
Wallet Case			
Power Source (Approx. Life)	Solar/LR1130 x 1	LR1130 x 1 (1 yr.)*4	
Dimensions (W x D x H)	71 x 116 x 16.5 mm 2-25/32" x 4-9/16" x 21/32"	60 x 103 x 8.3 mm 2-3/8" x 4-1/16" x 5/16"	
Weight (Approx.)	58 g	35 g	

# Specifications (Desktop, Semi-Desktop, Nice Sice)

Model	EL-2125C	
Display	12	
3-Digit Punctuation	0	
Memory	1 + GT	
Resume Function	0	
Line Counter	_	
Answer Check	O <sub>*1</sub>	
+Tax/-Tax Calculation	0/0	
Day/Date Calculation	_	
Conversion Function	3-rate	
Root	_	
Percent	0	
Sign Change	0	
Mark Up	_	
Grand Total	O*2	
Constant	0	
Time Calculation	_	
Auto Power Off	0	
Double Zero Key	0	
Triple Zero Key	_	
2-Key Roll-Over	0	
Decimal Setting	F-5-4-3-2-1-0-A	
Round Up/Off/Down	Off/Down	
Right Shift	0	
Kick Stand	_	
Tilt Display/Slant Display	0/-	
Power Source	Solar/LR44 x 1	
Dimensions (W x D x H)	140 x 195 x 22.5 mm 5-19/32" x 7-21/32" x 29/32"	
Weight (Approx.)	215 g	

Model	EL-338G
Display	12
3-Digit Punctuation	0
Memory	1 + GT
Answer Check	-
Cost/Sell/Margin	0
+Tax/-Tax Calculation	0/0
Root	-
Percent	0
Sign Change	-
Grand Total	0
Constant	0
Time Calculation	-
Auto Power Off	0
Double Zero Key	-
2-Key Roll-Over	0
Decimal Setting	F-3-2-0-A
Round Up/Off/Down	Off/Down
Right Shift	-
Kick Stand	-
Tilt Display/Slant Display	0/-
Power Source	Solar/LR44 x 1
Dimensions (W x D x H)	135 x 200 x 17 mm 5-5/16" x 7-7/8" x 21/32"
Weight (Approx.)	220 g

<sup>\*1</sup> Includes "Round Off" mode.

	niciaacs	rtouria	OII	mouc.	
*2	Includes	"Round	Off/	'Down"	modes.

Model	EL-337C	EL-421M	EL-334F
Display	12	14	10
3-Digit Punctuation	0	0	0
Memory	1 + GT	1	1 + GT
Resume Function	0	0	-
Line Counter	-		-
Answer Check	0,1		-
Cost/Sell/Margin	-		-
+Tax/-Tax Calculation	0/0	0/0	0/0
Day/Date Calculation	-		-
Conversion Function	3-rate		-
Root	-		-
Percent	0	0	0
Sign Change	0	0	0
Mark Up	-	_	-
Grand Total	0*2	_	0
Constant	0	0	0
Auto Power Off	0	0	0
Double Zero Key	0	0	0
2-Key Roll-Over	0	0	0
Decimal Setting	F-3-2-0-A	_	-
Round Up/Off/Down	Off/Down		-
Right Shift	-	0	0
Kick Stand	-	0	0
Tilt Display/Slant Display	0/-		-/-
Power Source	Solar/LR44 x 1	Solar/LR44 x 1	Solar/LR44 x 1
Dimensions (W x D x H)	108 x 175 x 22 mm 4-7/32" x 6-7/8" x 7/8"	108 x 170 x 15 mm 4-1/4" x 6-11/16" x 19/32"	108 x 170 x 15 mm 4-1/4" x 6-11/16" x 19/32"
Weight (Approx.)	165 g	160 g	160 g

<sup>\*1</sup> Includes "Round Off" mode. \*2 Includes "Round Off/Down" modes.

# Specifications (Mini Nice Sice)

Model	EL-332A	EL-310A	EL-M711G	EL-M700G
Display	10	8	10	8
3-Digit Punctuation	0		0	0
Memory	1	1	1	1
+Tax/-Tax Calculation	0/0	_/_	0/0	0/0
Conversion Function	-	_	0	_
Root	-	0	-	_
Percent	0	0	0	0
Sign Change	0	0	0	_
Constant	0	0	0	0
Auto Power Off	0	0	0	0
Double Zero Key	0	_	0	_
2-Key Roll-Over	0	_	0	0
<b>Decimal Setting</b>	-	-	+	_
Tilt Display/Slant Display	<b>-</b> /O	<del>-/</del> 0	-/0	<del>-</del> /0
Power Source	Solar/LR44 x 1	Solar/LR1130 x 1	Solar/LR44 x 1	Solar/LR44 x 1
Dimensions (W x D x H)	101 x 142 x 34 mm 3-31/32" x 5-19/32" x 1-11/32"	87 x 116 x 20 mm 3-13/32" x 4-9/16" x 25/32"	100 x 151.5 x 33 mm 3-15/16" x 5-31/32" x 1-5/16"	87 x 116.5 x 28.5 mm 3-7/16" x 4-19/32" x 1-1/8"
Weight (Approx.)	115 g	76 g	130 g	85 g

Kids **Calculators** 

Specifications

# Specifications

Model	EL-S10(PK/BL)
Display	8
3-Digit Punctuation	U
Memory	1
Root	0
Percent	U
Sign Change	U
Constant	O
<b>Decimal Setting</b>	_
2-Key Roll-Over	-
Auto Power Off	U
Slant Display	-
Key Material	Plastic
Hard Cover	U
Power Source (Approx. Life)	LR1130 x 1 (1 yr.)* <sup>1</sup>
Dimensions (W x D x H)	70 x 107 x 10.5 mm* <sup>2</sup> 2-3/4" x 4-7/32" x 13/32"
Weight (Approx.)	54 g

<sup>\*1</sup> When used for 1 hour per day.

Actual battery life may vary depending on usage. \*2 When closed.

# Specifications (Nice Sice, Mini Nice Sice, Hand-Held/Hard Cover)

Model	EL-145A	EL-144A	EL-143S
Display	14	14	14
3-Digit Punctuation	O	0	O
Memory	1	1	1
+Tax/-Tax Calculation	0/0	0/0	-/-
Root	-	_	U
Percent	O	0	O
Sign Change	U	_	-
Constant	U	U	U
Auto Power Off	U	U	U
Double Zero Key	U	U	U
2-Key Roll-Over	0	0	0
Right Shift	U	U	U
Tilt Display/Slant Display	U/-	U/-	-/-
Hard Cover	-	_	U
Power Source	Solar/LR44 x 1	Solar/LR44 x 1	Solar/LR1130 x 1
Dimensions (W x D x H)	110 x 168 x 15 mm 4-11/32" x 6-5/8" x 19/32"	102 x 148 x 15 mm 4-1/32" x 5-13/16" x 19/32"	72 x 115 x 12 mm 2-27/32" x 4-17/32" x 15/32"
Weight (Approx.)	160 g	125 g	66 g



pecirications Aerchandisingnformation

# Merchandising Information

Quantity/CTN may differ depending on sales region.

	INDIVIDUAL CARTON		IN	NER CART	ON			MASTER	CARTON					
MODEL	PACKAGE	G/W (kg)	DIM	ENSIONS	(mm)		G/W (kg)			G/W (kg)	DIM	ENSIONS	(mm)	
	ТҮРЕ	(Approx.)	DEPTH	WIDTH	HEIGHT	Q'ty/CTN	(Approx.)	М3	Q'ty/CTN	(Approx.)	DEPTH	WIDTH	HEIGHT	М3
Voice Recorde	ers													
PA-VR10EPCE	Box	0.15	175	98	32	10	1.60	0.007385	40	7.3	397	357	254	0.036000
PA-VR5E	Box	0.15	175	98	32	10	1.60	0.007385	40	7.3	397	357	254	0.036000
Electronic Or	8													
ZQ-P20H	Clamshell	0.45	263	196	52	10	4.80	0.023755	40	20.9	556	448	427	0.106361
ZQ-P10	Blister Pack	0.15	237	170	26	10	1.70	0.0125257	80	15.6	542	516	418	0.116903
Scientific Cal	·													
EL-506WWH	Box + Strap	0.19	161	83	30	10	2.00	0.004958	80	16.8	363	335	382	0.046454
EL-520WWH	Box + Strap	0.19	161	83	30	10	2.00	0.004958	80	16.8	363	335	382	0.046454
EL-531WHWH	Box + Strap	0.19	161	83	32	10	2.10	0.005266	80	17.7	363	355	382	0.049227
EL-501WWH	Box + Strap	0.13	150	82	24	10	1.50	0.004224	80	12.0	526	350	234	0.043080
EL-5120	Box + Strap	0.30	186+20	118	35	10	3.20	0.00969	40	13.8	414	386	300	0.047942
Printing Calc	`									16 1	F 10	450	460	0.100000
EL-2607P	Box	2.47	438	265	136		_	_	6	16.4	548	456	433	0.108201
EL-2901RH	Box	1.36	362	228	110		_	_	6	9.3	476	384	367	0.067082
EL-2901PIII	Box	1.3	342	239	85		_	_	5	7.5	463	367	274	0.046558
EL-1801C EL-1611P	Box + Strap	0.80	297+30 265+35	218 125	78 55		_	_	10 10	8.8 4.4	452 298	319 285	419 286	0.060415 0.024290
CS-Z635RH	Box + Strap		425	239	125		_	_	6	16.9	610	446	418	
Office Calcul	-	2.55					_	_	b	16.9	610	440	418	0.113721
EL-2125C	Box + Strap	0.26	199+20	144	27	10	2.70	0.010018	40	11.7	446	300	366	0.048971
EL-2123C EL-338G	Box + Strap	0.25	203+20	135	21	10	2.70	0.010018	40	11.7	454	240	348	0.048971
EL-337C	Box + Strap	0.20	180+20	112	26	10	2.20	0.007398	40	9.6	406	291	302	0.035680
EL-337C EL-421M	Box + Strap	0.20	173	115	24	10	2.20	0.006387	40	9.6	388	270	308	0.032266
EL-334F	Box + Strap	0.20	173+20	115	24	10	2.20	0.006387	40	9.6	388	270	308	0.032266
EL-332A	Box + Strap	0.15	145+20	104	31	10	1.60	0.006492	40	7.2	340	338	286	0.032867
EL-310A	Box + Strap	0.10	116+20	90	23	10	1.10	0.003524	40	5.0	278	260	258	0.018648
EL-M711G	Window box + Strap	0.24	219	142	36	10	2.67	0.015128	40	11.9	498	400	364	0.072509
EL-M700G	Window box + Strap	0.17	183	128	32	10	1.81	0.010535	40	8.2	426	360	366	0.051529
Personal Calo					-		2,02	0.02000		0.11				0.002000
EL-250S	Box + Strap	0.07	118+20	74	19	40	2.90	0.009955	160	12.4	422	326	354	0.048700
EL-233S	Blister Pack	0.05	180	122	14	40	2.60	0.012947	160	11.9	529	284	424	0.063700
EL-480SR	Box + Strap	0.11	128	78	18	40	4.60	-	160	19.4	394	335	354	0.046724
EL-W211G	Window box + Strap	0.12	183	106	16	40	4.92	0.018376	160	21.0	470	370	496	0.086254
EL-376S	Box + Strap	0.08	118+20	75	15	40	3.50	0.008087	160	14.9	342	330	354	0.039952
EL-243S	Box + Strap	0.07	108+20	67	15	40	2.20	0.006804	160	9.4	342	298	334	0.034040
Kid's Calcula	tors (NICE SIZ	ZE, MINI NI	CE SIZE, H	AND-HELD	/HARD COV	/ER)								
EL-S10	Blister Pack	0.08	191	122	22	10	0,95	0.005766	40	4.2	409	239	290	0.028348
14 Digit Calc					ELD/HARD	COVER)								
EL-145A	Box + Strap	0.18	169+20	108	23	10	1.90	0.005789	40	8.3	386	260	294	0.029506
EL-144A	Box + Strap	0.13	151+20	102	19	10	1.40	0.004158	40	6.0	350	220	282	0.021714
EL-143A	Box + Strap	0.08	118+20	75	15	40	3.50	0.008087	160	14.9	342	330	354	0.039952

# Merchandising Information

# Accessories and options

#### **■ AC ADAPTER**

Model		EA-28A	
Applicable model	EL-2626H	EL-1801L	EL-1611L
	EL-1801C	EL-1750P	EL-1611P

#### **■ HALF-SIZE RAM CARD with BATTERY**

Model	CE-2H16M*1
Applicable model	PC-E500S

#### **■ INK RIBBON**

Model	URBNT1007CCZZ					
Applicable model	CS-4194 CS-4194H CS-4194HC CS-2195L CS-2194	EL-2631L EL-2630L EL-2630P II EL-2615G EL-2607P				

#### **■ PAPER ROLL**

Model		EA-7100P*3				
Applicable	CS-4194	EL-2910R	EL-2630L	EL-1801C	EL-1607R	EL-1611L
model	CS-4194H	EL-2902C	EL-2626H	EL-1801L	EL-1195L	EL-1611P
	CS-4194HC	EL-2901C	EL-2615G	EL-1750P		
	CS-2195L	EL-2901RH	EL-2607R	EL-1611L		
	CS-2194	EL-2631L	EL-2195L	EL-1611P		

#### **■ INK ROLLER**

Model	EA-732R	EA-772R	EA-781R-BK/EA-781R-RD*4	EA-741R
Applicable model	EL-1801L EL-1611P EL-1611L	EL-2901RH EL-1750P EL-2626H	EL-2910R EL-2901C EL-1801C EL-1195L EL-2902C EL-2195L EL-1607P	EL-2607R EL-1607R

#### **■ ACCESSORY LINK KIT**

#### **PC-Link Software & Cable**

Model	CE-491FD (without cable) *5		(	CE-491W*	5, 7		CE-690W (cable option) *5	CE-LK2*5	CE-LK1P*8
Applicable model	EL-6890P*6 EL-6790P*6 ZQ-480P*6 ZQ-190P*6 ZQ-180P*6	EL-6850 EL-6750 EL-6690 EL-6660 ZQ-5900	ZQ-5400 ZQ-470 ZQ-4600 ZQ-4500 ZQ-4400	ZQ-4300 ZQ-4200 ZQ-4000 ZQ-3200 ZQ-3000	ZQ-2800 ZQ-2700 ZQ-2600 ZQ-2500 ZQ-170	ZQ-160 ZQ-150	ZQ-8600 ZQ-6800 ZQ-6600	EL-9900	EL-9650 EL-9600 EL-9450 EL-9400

#### **Docking Station**

Model	CE-60K*9/CE-61T*10						
Applicable model	ZQ-650	ZQ-640PC	ZQ-630PC				
	ZQ-650PC	ZQ-630	ZQ-570				

#### **Level Converter**

Model	CE-133T/CE-135T*11						
Applicable	ZQ-8600	ZQ-6600	ZQ-6000				
model	ZQ-6800	ZQ-6200					

#### **Set-to-Set Communication Cable**

Model	CE-300L (4-pin)					CE-451L (3-pin)	CE-450L (3-pin)	CE-260L*7(3-pin)	
Applicable model	EL-6690 EL-6660 ZQ-650 ZQ-650PC ZQ-640PC ZQ-630	ZQ-630PC ZQ-6200 ZQ-6000 ZQ-5900 ZQ-570 ZQ-570PC	ZQ-5400 ZQ-470 ZQ-4600 ZQ-4500 ZQ-4400 ZQ-4300	ZQ-4200 ZQ-4000 ZQ-3200 ZQ-3000 ZQ-2800 ZQ-2700	ZQ-2600 ZQ-2500 ZQ-170 ZQ-150	EL-9900	EL-9650 EL-9600 EL-9450 EL-9400	EL-6890P EL-6850 EL-6790P EL-6750 ZQ-480P ZQ-190P	ZQ-180P ZQ-160

<sup>\*1</sup> CE-2H16M: 16KB \*2 5 rolls/pack, 58 (W) × 80 (ø) mm \*3 58 (W) × 25 (ø) mm \*4 EA-781R-BK: Black, EA-781R-RD: Red

<sup>\*5</sup> English version only.

<sup>\*6</sup> Use either CE-491W or CE-491FD.
\*7 May not be available in some regions as stocks are very limited.

<sup>\*8</sup> English and French version only.

<sup>\*9</sup> English version only. With PC Link & PIM software.
\*10 Without software.
\*11 CE-133T: for IBM-PC (RS232C), CE-135T: for MAC (RS422)

# **SHARP**

Sharp Electronics Central & Eastern Europe, a division of Sharp Europe A-1020 Vienna, Handelskai 342, Phone: +43 / (0)1 / 7 27 19 - 0 Fax: +43 / (0)1 / 7 27 19 - 141, e-mail: marketing@scee.sharp-eu.com more info at: www.sharp-cee.com

- Design and specifications are current as of September 2005, but are subject to change without prior notice.
- All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers. Sharp makes no warranties or representations of any kind with respect to these products.
- Some peripheral products may not be available in some regions. Screen displays are simulated.
  Some models may not be available in some regions.
- Please ask your Sharp dealer for details.

Distributed by: